




SOLAR LIGHTING  
MORITA DENKI.CO.,LTD  
602 uesuto 2-2-2daiba,  
minatoku,tokyotou,135-0091 JAPAN  
TEL:+813-3527-6771 FAX:+813-3527-6771  
E-mail:tyou@mrt-electric.com

*Solar our Life.*

2018.01



[www.mrt-electric.com](http://www.mrt-electric.com)

SOLAR  
LIGHTING

*Solar our Life.*

# SOLAR LIGHTING



## PRODUCT RANGE

### Hot and Classic Series

- TITANS Series
- HONOR Series
- ATLAS Series
- CLASSIC Series
- ARGES Series
- THERMERS Series
- UFO Series
- Pearl Series
- Wall Light Series
- Wall Washer Light Series





2018

TOKYO JAPAN

# OUR OFFICE

PRETTY OFFICE ENVIRONMENT



## COMPANY PROFILE

2018年に株式会社モリタ電器は、おかげさまで「創業37周年」を迎えました。これもひとえに、皆様の温かいご支援の賜物と心より感謝申し上げます。

今、株式会社モリタ電器は第2の創業期を迎えています。これからのモリタ電器は長期ビジョンとして「技術力ある100年企業」を目指します。

先行きが不透明な世界経済ですが、株式会社モリタ電器は急速かつ確実に進化していきます。この変化は株式会社モリタ電器にビジネスチャンスをもたらします。

さらに「長期構想」を策定し、お客様と共に将来の成長への道を描いています。これからも私たちは、常にお客様の立場に立ち、お客様起点の経営に徹し、多くのお客様にお役に立てるしくみづくりに取り組んで参ります。



CEO 張 曉丹 (XiaoDan Zhang)


日本大学 商学部卒業

青山学院大学 国際マネジメント研究科 (MBA)





## OUR CERTIFICATES



ISO9001

Intertek Report

SASO



CE Certification

FCC Certification

ROHS Certification

## OUR PATENT



SLL-03 Patent

SGL-01 Patent

Supplier Assessment  
BV Report



SML-01 Patent

SML-02 Patent

ESL-24 Patent

## OUR FACTORY



WAREHOUSE


PRODUCTION LINE



TEST EQUIPMENT



Battery Aging Test



Battery aging test



LED aging testings



Outdoor Testing area



LED brightness test



Waterproof testing



XJCM-SUN SIMULATOR



04



# TITANS SERIES

Right Choice for  
government project!

*Solar our Life.*





SSL-28N/27N/26N/25N/24N/23N/22N

## TITANS SERIES SOLAR STREET LIGHT



-15 Degree



0 Degree




15 Degree




30 Degree



Lateral View



Lamp Front View



Solar Panel



**80W**

**SSL-28N**

2258\*810\*385mm

**70W**

**SSL-27N**

2096\*810\*385mm

**60W**

**SSL-26N**

1875\*810\*385mm

**50W**

**SSL-25N**

1687\*810\*385mm

**40W**

**SSL-24N**

1770\*421\*385mm

**30W**

**SSL-23N**

1530\*421\*385mm

**20W**

**SSL-22N**

1116\*421\*385mm

Multi-Angle

-15,0,15,30 Four-degree angle to confirm the most effective charging efficiency. Professional Lighting distribution can keep the same angle while the Solar Panel angle changing.

Patent

Professional Fresnel lens to achieve 20 m and 120 degree detectable area, far more than the competitor

Features


Aircraft Carrier design to enlarge the solar panel and battery. Provide a longer lighting time

Application

Street,Courtyard,Garden, Park,Roadway,pathway, Parking Lot,Campus,Farm & Ranch,Military Base

TITANS SERIES  
Remote Control  
Solar Street Light

Different Angle and High efficiency Charge,  
Never Affected by the Installation Position.



Model	SSL-22N	SSL-23N	SSL-24N	SSL-25N	SSL-26N	SSL-27N	SSL-28N
LED	20W	30W	40W	50W	60W	70W	80W
Solar Panel	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon
Battery Type	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery
Solar Charging Time	9-10 hours by bright sunlight	9-10 hours by bright sunlight	9-10 hours by bright sunlight	10 hours by bright sunlight	10 hours by bright sunlight	10 hours by bright sunlight	10 hours by bright sunlight
Lighting Time	4~7 Nights after fully Charged	4~7 Nights after fully Charged	4~7 Nights after fully Charged	4~7 Nights after fully Charged	4~7 Nights after fully Charged	4~7 Nights after fully Charged	4~7 Nights after fully Charged
Lighting Mode	10 types	10 types	10 types	10 types	10 types	10 types	10 types
Material	Aluminumalloy + PC	Aluminumalloy + PC	Aluminumalloy + PC	Aluminumalloy + PC	Aluminumalloy + PC	Aluminumalloy + PC	Aluminumalloy + PC
Waterproof	IP65	IP65	IP65	IP65	IP65	IP65	IP65
Product Size	1116*421*385mm	1530*421*385mm	1770*421*385mm	1687*810*385mm	1875*810*385mm	2096*810*385mm	2258*810*385mm
Application	Street,Courtyard,Garden, Park,Roadway,pathway,Parking Lot,Campus,Farm & Ranch,Military Base						



## SSL-10N/11N



**Back to 18th century !**

**HONOR SERIES  
SOLAR LANDSCAPE LIGHT**



**20W**  
SLL-10N  
2.5M



**20W**  
SLL-11N  
2.5M



Model	SLL-10N	SLL-11N
LED	<b>20W</b>	<b>20W</b>
Solar Panel	Monocrystalline silicon	Monocrystalline silicon
Battery Type	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery
Solar Charging Time	5-6 hours by bright sunlight	5-6 hours by bright sunlight
Lighting Time	4~7 Nights after fully Charged	4~7 Nights after fully Charged
Lighting Mode	2 types	2 types
Material	Aluminum alloy + PC	Aluminum alloy + PC
Waterproof	IP65	IP65
Product Size	Φ416*830mm	Φ416*808mm
Application	Garden, Gate, Fence, Courtyard, Road, Park, Pathway etc	



# ATLAS Series

## Solar Street Light

10 cloudy days still lighting !





**ATLAS Series**  
**Solar Street Light**  
**10 cloudy days still lighting !**



# SSL-32/33/34/35/36/37/38/39/310



## ATLAS Series



Model	SSL-32	SSL-33	SSL-34	SSL-35	SSL-36	SSL-37	SSL-38	SSL-39	SSL-310
LED	20W	30W	40W	50W	60W	70W	80W	90W	100W
Solar Panel	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon
Battery Type	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery
Solar Charging Time	7~10 hours by bright sunlight	7~10 hours by bright sunlight	7~10 hours by bright sunlight	7~10 hours by bright sunlight	7~10 hours by bright sunlight	7~10 hours by bright sunlight	7~10 hours by bright sunlight	7~10 hours by bright sunlight	7~10 hours by bright sunlight
Lighting Time	7~10 nights after fully charged	7~10 nights after fully charged	7~10 nights after fully charged	7~10 nights after fully charged	7~10 nights after fully charged	7~10 nights after fully charged	7~10 nights after fully charged	7~10 nights after fully charged	7~10 nights after fully charged
Lighting Mode	3 types	3 types	3 types	3 types	3 types	3 types	3 types	3 types	3 types
Material	Aluminum alloy	Aluminum alloy	Aluminum alloy	Aluminum alloy	Aluminum alloy	Aluminum alloy	Aluminum alloy	Aluminum alloy	Aluminum alloy
Waterproof	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP65
Product Size	678*303*84.3mm	812*303*84.3mm	963*303*84.3mm	1327*303*84.3mm	1096*381*95.3mm	1327*381*95.3mm	1563*381*95.3mm	1563*381*95.3mm	1563*381*95.3mm
Application	Street,Courtyard,Garden, Park,Roadway,pathway,Parking Lot,Campus,Farm & Ranch,Military Base								

# CLASSIC SERIES

Forever Classic ,  
never exceeded !  
- Solar Street cLight



SSL-01N/02N/03N/04N/05N



Forever Classic, never exceeded !  
All In One Solar Street Courtyard Light




Specification					
Model	SSL-01N	SSL-02N	SSL-03N	SSL-04N	SSL-05N
LED	10W	20W	30W	50W	80W
Battery Type	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion battery	Rechargeable Li-ion battery
Solar Panel	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon
Install height	2.5~3meters	3~4 meters	4~5 meters	4~6M	6~8M
Solar charging time	11 hours by bright sunlight	9~10 hours by bright sunlight	9~10 hours by bright sunlight	10 hours by bright sunlight	10~11 hours by bright sunlight
Lighting time	4~7 nights	4~7 nights	4~7 nights	Over 4~7 nights	Over 4~7 nights
Lighting mode	2 types	2 types	2 types	2 types	2 types
Waterproof	IP 65	IP 65	IP 65	IP65	IP65
Material	Aluminum alloy + steel glass	Aluminum alloy + steel glass	Aluminum alloy + steel glass	Aluminum alloy + toughened glass	Aluminum alloy + toughened glass
Size	505*227*164mm	808*227*164mm	1098*227*164mm	1553*420.5*224.5mm	1933*420.5*224.5 mm
Application	Street,Courtyard,Garden,Park, Roadway,Pathway,Parking Lot,Privateroad, Sidewalk,Public square, plaza,Campus,Airfield,Farm & Ranch,Perimeter Security, Wildlife area,Remote Area,Military Base				



# ARGES SERIES

Standout  
everywhere  
as you see!

- Solar Street Light



## SSL-06N/07N/08N/09N



Standout everywhere as you see !

Remote Control  
Argès Series Solar Street Light



Model	SSL-06N	SSL-07N	SSL-08N	SSL-09N
LED	30W	45W	60W	100W
Solar Panel	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon
Battery Type	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery
Solar Charging Time	9-10 hours by bright sunlight	9-10 hours by bright sunlight	10 hours by bright sunlight	10 hours by bright sunlight
Lighting Time	4-7Nights after fully Charged	4-7Nights after fully Charged	4-7Nights after fully Charged	4-7Nights after fully Charged
Lighting Mode	remote control 38 types	remote control 38 types	remote control 38 types	remote control 38 types
Material	Aluminumalloy + PC	Aluminumalloy + PC	Aluminumalloy + PC	Aluminumalloy + PC
Waterproof	IP65	IP65	IP65	IP65
Product Size	773*225*287mm	1043*225*287mm	1511*225*616mm	1933*420.5*224.5mm
Application	Street,Courtyard,Garden,Park,Roadway,pathway,Parking Lot,Campus,Farm,Ranch,Military Base.			

# ESL-20N/30N/40N



**Brighter than brighter !**

All-in-One Solar street LED light



**20W**

ESL-20N

**30W**

ESL-30N

**40W**

ESL-40N



## Specification

Model	ESL-20N	ESL-30N	ESL-40N
LED	<b>20W</b>	<b>30W</b>	<b>40W</b>
Battery Type	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery
Solar Panel	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon
Install height	4~5 meters	4~6 meters	6~8 meters
Solar charging time	9~10 hours by bright sunlight	9~10 hours by bright sunlight	9~10 hours by bright sunlight
Lighting time	3~5 nights after fully charged	3~5 nights after fully charged	3~5 nights after fully charged
Lighting mode	2 types	2 types	2 types
Waterproof	IP 65	IP 65	IP 65
Material	Aluminum alloy +PC		
Size	1092*488*117mm	1092*488*117mm	1308*488*117mm
Application	Street, Government project, Garden, Courtyard, Roadway, Pathway, Public square, Campus, Parking lot		





# UFO Series

Simple,  
The Best View !  
- Solar Plaza Light



SLL-12N/14N/16N

Simple, the best view !

Remote Control  
UFO Series Solar Plaza Light



Specification			
Model	SLL-12N	SLL-14N	SLL-16N
LED	20W	30W	50W
Battery Type	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery
Solar Panel	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon
Install height	3~4 meters	3~5 meters	4~6 meters
Solar charging time	7-8 Hours by Bright Sunlight	8-9 Hours by Bright Sunlight	9-10 Hours by Bright Sunlight
Lighting time	4~7 nights	4~7 nights	4~7 nights
Lighting mode	remote control 38 types	remote control 38 types	remote control 38 types
Waterproof	IP 65	IP 65	IP 65
Material	Aluminum alloy+ABS	Aluminum alloy+ABS	Aluminum alloy+ABS
Size	525*525*161mm	690*727*223 mm	935*905*234mm
Application	Courtyard, Garden, Park, Street, Roadway, Pathway, Parking Lot, Private Road, Sidewalk, Public Square, Plaza, Campus, Airfield, Farm, Ranch & Ranch, Perimeter Security, Wildlife Area, Remote Area, Military Base		

Professional Lighting Distribution for Government Project

**SCL-01N**



**Choices in your hands !**

**Remote controller+  
Solar Courtyard Light**

**10W**



Specification	
LED	10W
Solar panel	Monocrystalline silicon
Battery Type	Rechargeable Li-ion Battery
Solar charging time	9-10 Hrs by bright sunlight
Lighting time	4~7 nights
Lighting mode	38 types
Material	Aluminum alloy + PC
Waterproof	IP65
Product size	446*247*86mm
Application	Garden, Courtyard



**SLL-21**



**Back to 18th century !**

**Solar Landscape Light**

**20W**



Specification	
LED	20W
Solar panel	Monocrystalline silicon
Battery Type	Li-ion rechargeable battery
Solar charging time	8-9 hours by bright sunlight
Lighting time	4~7 nights
Lighting mode	DIM Light with PIR
Material	Aluminum alloy + PC
Waterproof	IP65
Product size	512*512*482mm
Application	Plaza, Public Square, Courtyard, Garden, Park, Street, Roadway, pathway, Parking Lot, Private road, Sidewalk, Campus, Airfield, Farm & Ranch



**25W**



**SDL-01R**



**Choices in your hands !**

**Remote controller+  
Solar Courtyard Light**



Specification	
LED	25W
Solar panel	Monocrystalline silicon
Battery Type	Li-ion rechargeable battery
Solar charging time	12-13 hours by bright sunlight
Lighting time	4~7 nights
Lighting mode	38 types
Material	Aluminum + ABS
Install height	3 meters
Waterproof	IP 65
Product size	752*459*153mm
Application	Courtyard, Garden, Park, Street, Roadway, pathway, Parking Lot, Private road, Sidewalk, Public square, plaza, Campus, Airfield, Farm & Ranch, Perimeter Security, Wildlife area, Remote Area, Military Base



# PEARL SERIES

**Illuminate  
your secret  
garden !**

- Solar Garden Light



## ESL-15N/25N



**Illuminate your secret garden !**  
Pearl Series Solar Garden Light



Specification		
Model	ESL-15N	ESL-25N
LED	1W	1W
Solar panel	Monocrystalline silicon	Monocrystalline silicon
Battery Type	Li-ion rechargeable battery	Li-ion rechargeable battery
Solar charging time	7~8 hours by bright sunlight	7~8 hours by bright sunlight
Lighting time	4~7 nights	4~7 nights
Lighting mode	2 types	2 types
Material	Aluminum alloy+ABS+PC	Aluminum alloy+ABS+PC
Waterproof	IP65	IP65
Product size	160*160*264mm	160*160*800mm
Application	Garden, Courtyard, Road, Park, Street, Pathway	



## SDL-02



**Illuminate your secret garden !**  
Pearl Series Solar Garden Light



Specification	
LED	20Lumens
Solar panel	Monocrystalline silicon
Battery Type	Rechargeable Li-ion Battery
Solar charging time	9-10Hrs by bright sunlight
Lighting time	3 Nights after fully Charged
Lighting mode	High Light for 8 Hours Per Night
Material	Aluminum alloy + PC
Waterproof	IP65
Product size	Diameter 124mm, Pole:620mm
Application	Garden, Courtyard, Park, lawn, Swimming pool



## SGL-01N/02N



**Illuminate your secret garden !**  
Pearl Series Solar Garden Light



Specification		
Model	SGL-01N	SGL-02N
LED	1W	4W
Battery Type	Rechargeable Li-ion battery	Rechargeable Li-ion battery
Solar panel	Monocrystalline silicon	Monocrystalline silicon
Solar charging time	7~8 hours by bright sunlight	7~8 hours by bright sunlight
Lighting time	4~7 nights	4~7 nights
Lighting mode	2 types	2 types
Material	Aluminum+PC	Aluminum+PC
Waterproof	IP65	IP65
Product size	176 *176 *277mm	176 *176 *802mm
Application	Garden, Courtyard, Road, Park, Hotel, Pathway etc	

## SGL-03N/04N



**Illuminate your secret garden !**  
Pearl Series Solar Garden Light



Specification		
Model	SGL-03N	SGL-04N
LED	4W	4W
Battery Type	Rechargeable Li-ion battery	Rechargeable Li-ion battery
Solar panel	Monocrystalline silicon	Monocrystalline silicon
Solar charging time	7~8 hours by bright sunlight	7~8 hours by bright sunlight
Lighting time	4~7 nights	4~7 nights
Lighting mode	2 types	2 types
Material	Aluminum+PC	Aluminum+PC
Waterproof	IP65	IP65
Product size	176 *176 *438mm	250 *176 *298mm
Application	Garden, Courtyard, Road, Park, Hotel, Pathway etc	





## SWL-01N



**Take me home, my Hyperion !**  
Solar Motion Light

**10W**



### Specification

LED	10W
Solar panel	Monocrystalline silicon
Battery Type	Rechargeable Li-ion Battery
Solar charging time	8 - 9 Hours by Bright Sunlight
Lighting time	4~7 nights
Lighting mode	2 types
Material	Aluminum Alloy + ABS
Install height	2-3M
Waterproof	IP65
Product size	282*185*205mm
Application	Warehouse, Courtyard, Community, Parking Lot Wall, Building Wall, Garden, Park, Square, Pathway, etc.

## SML-01N/SML-01T



**Take me home, my Hyperion !**  
Remote Control Solar  
PIR Security Light



### Specification

Model	SML-04N	SML-01T
LED	10W	10W
Solar panel	Monocrystalline silicon, 17% efficiency	Monocrystalline silicon, 17% efficiency
Battery Type	Li-ion rechargeable battery	Li-ion rechargeable battery
Solar charging time	11 hours by bright sunlight	11 hours by bright sunlight
Lighting time	7 nights	7 nights
Lighting mode	2 types	remote control
Material	Aluminum alloy+toughened glass	Aluminum alloy+toughened glass
Install height	2.5~3.5M	2.5~3.5M
Waterproof	IP65	IP65
Work temperature	-25℃ to 65℃	-25℃ to 65℃
Product size	242.5*120.5*92mm	242.5*120.5*92mm
Application	Warehouse, Garden, park, courtyard, community, building, Wall, etc	



## SWL-02N



**Take me home, my Hyperion !**  
Solar Motion Light

**4W**



### Specification


LED	4W
Solar panel	Monocrystalline silicon
Battery Type	Rechargeable Li-ion Battery
Solar charging time	9 - 10 Hours by Bright Sunlight
Lighting time	3 Nights after Fully Charged
Lighting mode	2 types
Material	ABS+PC
Waterproof	IP65
Install height	2-3M
Product size	131*234*101mm
Application	Warehouse, Courtyard, Community, Parking Lot Wall, Building Wall, Garden, Park, Square, Pathway, etc.

## SML-02

Take me home , my Hyperion !  
Solar Wall light



Specification	
LED	200Lumens
Solar panel	Monocrystalline silicon
Battery Type	Li-ion rechargeable battery
Solar charging time	12 hours by bright sunlight
Lighting time	Over 3 nights
Lighting mode	Warm White Dim Lighting +Motion Sensor for Bright Pure White Lighting
Material	ABS+PC
Install height	2~3M
Waterproof	IP65
Product size	N/A
Application	Garden, Courtyard, Road,Park, Street,Pathway



## ESL-06K

Take me home , my Hyperion !  
Solar Wall light



Specification	
LED	20Lumens
Solar panel	Monocrystalline silicon
Battery Type	Li-ion rechargeable battery
Solar charging time	12 hours by bright sunlight
Lighting time	Over 3 nights
Lighting mode	High brightness for the hole night
Material	Aluminum+ABS
Waterproof	IP65
Product size	200*123*63mm
Application	Wall, Step, Road, Garden, Park, Square, Street , Pathway




Warm White

## SLL-05/SLL-15

Light your way home !  
Solar underground light



SLL-05/15



Specification			
Model	ESL-01	SLL-05	SLL-15
LED	20Lumens	30Lumens	30Lumens
Solar panel	Monocrystalline silicon	Monocrystalline silicon	Monocrystalline silicon
Battery Type	Li-ion rechargeable battery	Li-ion rechargeable battery	Li-ion rechargeable battery
Solar charging time	7 hours by bright sunlight	11 hours by bright sunlight	11 hours by bright sunlight
Lighting time	High bright light 50Hrs	3 nights after fully charged	3 nights after fully charged
Lighting mode	High brightness for whole night	First 5 hours white color light, when something pass by above the lamp (distance 0-50CM), it will turn to blue color for 5-10 second. After the first 5 hours,color switch sensor will turn off automatically and the lamp keep white color in 50% DIM light. After 10 hours lighting, the lamp will be off automatically.	
Material	Aluminum alloy + Tempered Glass		
Waterproof	IP68	IP68	IP68
Product size	Φ128*58mm	Φ170*55mm	Φ170*55mm
Application	Plaza, Park, Garden, Street, Walkway, Bank of swimming pool etc.		

## SLL-02

RGB Solar Flood Light



Specification	
LED	3W RGB LED
Solar panel	Monocrystalline silicon
Battery Type	Li-ion rechargeable battery
Solar charging time	8~9 hours by bright sunlight
Lighting time	2 nights
Lighting mode	5 hours 100% brightness and then 3 hours 50%, 8 hours per night. Red,Orange, Yellow,Green,Green Grass,Blue, Purple, Seven Colors Switch
Material	Aluminum alloy + Tempered Glass
Install height	N/A
Waterproof	IP65
Product size	242.5*120.5*92mm
Application	Courtyard,Garden, Park,Street,Roadway,pathway,Parking Lot,Private road,Sidewalk,Public square,plaza,Campus,Airfield,Farm & Ranch, Perimeter Security,Wildlife area,Remote Area,Military Base





东桥鸟瞰

# Solar Wall Washer Series

Advertising your  
advertisement !



**SLL-17**  
Advertising your advertisement !  
Solar Wall Washer Light

**4W**



Specification	
LED	4W
Solar panel	Monocrystalline silicon
Battery Type	Rechargeable Li-ion Battery
Solar charging time	6-7 hours by bright sunlight
Lighting time	3 Nights after fully Charged
Lighting mode	5Hrs high brightness + 3 Hrs dim light
Material	Aluminum alloy + PC
Waterproof	IP65
Product size	1022*128*108mm
Application	Garden,Hotel,Overpass, Bridge,Building External Wall , Yard,Square,Pathway,etc




**SLL-08**  
Advertising your advertisement !  
Solar Wall Washer Light

**2W**



Specification	
LED	2W
Solar panel	Monocrystalline silicon
Battery Type	Rechargeable Li-ion Battery
Solar charging time	6-7 hours by bright sunlight
Lighting time	3 Nights after fully Charged
Lighting mode	5Hrs high brightness + 3 Hrs dim light
Material	Aluminum alloy + PC
Waterproof	IP65
Product size	517*108*128mm
Application	Garden,Hotel,Overpass, Bridge,Building External Wall , Yard,Square,Pathway,etc





SSL-13A/13B/14A/14B/15A/15B/16A/16B

**Apollo Series**

Solar Hight Mast Light



140W

SSL-13A

SSL-13B



210W

SSL-14A

SSL-14B



250W

SSL-15A

SSL-15B



320W

SSL-16A

SSL-16B



15 Degree

0 Degree

Model	SSL-13A	SSL-13B	SSL-14A	SSL-14B	SSL-15A	SSL-15B	SSL-16A	SSL-16B
LED	14000 Lumens	14000 Lumens	21000 Lumens	21000 Lumens	25000 Lumens	25000 Lumens	32000 Lumens	32000 Lumens
Solar Panel	Monocrystalline Silicon	Monocrystalline Silicon	Monocrystalline Silicon	Monocrystalline Silicon	Monocrystalline Silicon	Monocrystalline Silicon	Monocrystalline Silicon	Monocrystalline Silicon
Battery Type	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery	Rechargeable Li-ion Battery
Solar Charging Time	10 - 12 Hours by Bright Sunlight	10 - 12 Hours by Bright Sunlight	10 - 12 Hours by Bright Sunlight	10 - 12 Hours by Bright Sunlight	10 - 12 Hours by Bright Sunlight	10 - 12 Hours by Bright Sunlight	10 - 12 Hours by Bright Sunlight	10 - 12 Hours by Bright Sunlight
Lighting Time	3 Nights after fully Charged	3 Nights after fully Charged	3 Nights after fully Charged	3 Nights after fully Charged	3 Nights after fully Charged	3 Nights after fully Charged	3 Nights after fully Charged	3 Nights after fully Charged
Lighting Mode	Wireless Control + Timer	Wireless Control + Timer	Wireless Control + Timer	Wireless Control + Timer	Wireless Control + Timer	Wireless Control + Timer	Wireless Control + Timer	Wireless Control + Timer
Material	Aluminum Alloy + PC	Aluminumalloy + PC	Aluminumalloy + PC	Aluminumalloy + PC	Aluminumalloy + PC	Aluminumalloy + PC	Aluminumalloy + PC	Aluminumalloy + PC
Waterproof	IP65	IP65	IP65	IP65	IP65	IP65	IP65	IP65
Product Size	1020*1020mm	1020*1020mm	1650*1020mm	1650*1020mm	1330*1330mm	1330*1330mm	1490*1490mm	1490*1490mm
Application	Public Square, Stadium, Parking Lot, Farm & Ranch, Mining Area, Port Wharf, Highway Exit, Highway Crossroad, Airport, Military Base							

Practical Application  
from Customer



More...

More Popular Solar products, please visit  
<http://www.mrt-electric.com/>

Some of our  
Exhibition



2012 South African Solar show



2013 Apri Hong-Kong Solar show



2014 Brazil International  
Lighting Industry Exhibition



2014 Mexico Expoelectrica  
Internacional



2014 Year Dubai International  
Design Exhibition



2015 Abu Dhabi National Exhibition



2015 Dubai Light Middle East



2015 SOLAR-TEC in Egypt



2015 Canton Fair



2015 Germany Intersolar Fair



2015 UK Fair



2015 Solar World Africa



2016 POGEE Pakistan



2016 SOLARED Istanbul Turkey



2016 Saudi Power